## NSN 5306-01-284-9683

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-284-9683

0.643 inches
Fastener Length:
Between 1.133 inches and 1.153 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Single Shear Strength:
132000 pounds per square inch
Thread Diameter:
0.375 inches
Grip Length:
0.500 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Nickel and cadmium and chromate
Surface Treatment Specification:
Ams 2416 assn standard single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-284-9683

Shear Bolt - Page 2 of 2



Specification [	)ata:
-----------------	-------

80205-nas1785 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0