

View Online at <https://aerobasegroup.com/nsn/5306-01-284-9896>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.762 inches and 0.792 inches

**Fastener Length:**

Between 2.200 inches and 2.230 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.450 inches

**Extended Washer Diameter:**

Between 0.922 inches and 0.932 inches

**Extended Washer Thickness:**

Between 0.062 inches and 0.082 inches

**Shoulder Diameter:**

0.4985 inches first shoulder and 0.4995 inches first shoulder

**Shoulder Length:**

1.187 inches first shoulder and 1.197 inches first shoulder

**Hole Diameter:**

0.055 inches

**End Application:**

Lantirn/f-16c&d

**Thread Diameter:**

0.438 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0