

View Online at <https://aerobasegroup.com/nsn/5306-01-285-5976>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.357 inches and 1.500 inches

**Fastener Length:**

Between 1.440 inches and 1.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.270 inches and 0.295 inches

**Width Between Flats:**

Between 0.552 inches and 0.562 inches

**Washer Quantity:**

1

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

45.0 rockwell c primary washer and 53.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.635 inches and 0.651 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

0.094 inches

**Special Features:**

Flat pointed end 40.0 degrees min. To 45.0 degrees max. Point chamfer angle

**Material:**

Steel comp 1060 primary washer

**Material Specification:**

Astm a684 assn standard single material response primary washer

**Surface Treatment:**

Cadmium and chromate or zinc and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 3 federal specification 1st treatment response or astm b633, type 2 cl fe/zn5 assn standard 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0