NSN 5306-01-285-5976

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-285-5976 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.357 inches and 1.500 inches **Fastener Length:** Between 1.440 inches and 1.500 inches **Head Style:** Hexagon **Head Height:** Between 0.270 inches and 0.295 inches Width Between Flats: Between 0.552 inches and 0.562 inches Washer Quantity: **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 45.0 rockwell c primary washer and 53.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.635 inches and 0.651 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.094 inches **Special Features:** Flat pointed end 40.0 degrees min. To 45.0 degrees max. Point chamfer angle Material: Steel comp 1060 primary washer **Material Specification:** Astm a684 assn standard single material response primary washer **Surface Treatment:** Cadmium and chromate or zinc and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification 1st treatment response or astm b633, type 2 cl fe/zn5 assn standard 2nd treatment response **Thread Series Designator:** Unf

N/a

Shelf Life:

NSN 5306-01-285-5976

Assembled Washer Bolt - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0