

View Online at <https://aerobasegroup.com/nsn/5306-01-285-8884>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.301 inches and 0.331 inches

**Fastener Length:**

Between 0.739 inches and 0.769 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.082 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

0.438 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.623 inches second hole and 0.653 inches second hole

**Product Name:**

Navy special project

**Material:**

Steel comp e4340

**Material Specification:**

Mil-s-5000, cond. C4 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.