NSN 5306-01-286-3104

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-286-3104

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.899 inches and 0.939 inches
Fastener Length:
Between 1.534 inches and 1.554 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.608 inches and 0.628 inches
Width Between Flats:
0.687 inches
Extended Washer Diameter:
Between 1.040 inches and 1.050 inches
Extended Washer Thickness:
Between 0.140 inches and 0.160 inches
Grip Diameter:
Between 0.6230 inches and 0.6240 inches
Thread Diameter:
0.625 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-286-3104

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0