

View Online at <https://aerobasegroup.com/nsn/5306-01-286-3104>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.899 inches and 0.939 inches

Fastener Length:

Between 1.534 inches and 1.554 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.608 inches and 0.628 inches

Width Between Flats:

0.687 inches

Extended Washer Diameter:

Between 1.040 inches and 1.050 inches

Extended Washer Thickness:

Between 0.140 inches and 0.160 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0