## NSN 5306-01-286-3507

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-286-3507 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.680 inches and 0.730 inches **Fastener Length:** Between 2.315 inches and 2.345 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.425 inches and 0.445 inches Width Between Flats: 0.502 inches **Extended Washer Diameter:** Between 0.740 inches and 0.750 inches **Extended Washer Thickness:** Between 0.089 inches and 0.109 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Thread Diameter:** 0.437 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Qq-p-35 federal specification single treatment response

**Passivate Surface Treatment Specification: Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

## NSN 5306-01-286-3507

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0