

View Online at <https://aerobasegroup.com/nsn/5306-01-286-7982>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.374 inches and 0.441 inches

Fastener Length:

Between 1.446 inches and 1.493 inches

Head Style:

Double hexagon

Head Height:

0.210 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Grip Diameter:

Between 0.3733 inches and 0.3742 inches

Shank Unthreaded Hole Diameter:

0.101 inches first hole and 0.111 inches first hole

Single Shear Strength:

132000 pounds per square inch

Thread Diameter:

0.375 inches

Grip Length:

Between 1.052 inches and 1.072 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.313 inches first hole and 1.345 inches first hole

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Nas672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0