

View Online at <https://aerobasegroup.com/nsn/5306-01-287-1577>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.085 inches and 1.135 inches

Fastener Length:

Between 3.407 inches and 3.437 inches

Head Style:

Spline extended washer

Head Height:

Between 0.552 inches and 0.572 inches

Extended Washer Diameter:

Between 1.153 inches and 1.163 inches

Extended Washer Thickness:

Between 0.068 inches and 0.080 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Head Minor Diameter:

Between 0.673 inches and 0.688 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 2.302 inches and 2.322 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 ty2 cl2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.