

View Online at <https://aerobasegroup.com/nsn/5306-01-287-3570>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.345 inches and 0.395 inches

**Fastener Length:**

Between 1.293 inches and 1.323 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.429 inches and 0.439 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.928 inches and 0.948 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Surface Treatment:**

Chromium

**Surface Treatment Specification:**

Qq-c-320 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6204 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.