NSN 5306-01-287-6617

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-287-6617
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.710 inches and 0.760 inches
Fastener Length:
Between 5.720 inches and 5.750 inches
Head Style:
Dished hexagon
Head Height:
Between 0.250 inches and 0.265 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 4.990 inches and 5.010 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

80205-nas6608 professional/industrial association standard

NSN 5306-01-287-6617

Shear Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-s-5000 spec.

Shelf Life: