NSN 5306-01-288-9350

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-288-9350

| Thread Direction: |
|--|
| Right-hand |
| Thread Length: |
| Between 40.5 millimeters and 41.5 millimeters |
| Fastener Length: |
| Between 260.75 millimeters and 261.25 millimeters |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 14.78 millimeters and 15.22 millimeters |
| Width Between Flats: |
| Between 35.38 millimeters and 36.00 millimeters |
| Grip Diameter: |
| Between 23.979 millimeters and 24.000 millimeters |
| Thread Diameter: |
| 24.0 millimeters |
| Grip Length: |
| Between 219.75 millimeters and 220.25 millimeters |
| Min. Tensile Strength (psi): |
| 1100 megapascals |
| Thread Pitch In Millimeters: |
| 2.0 |
| External Thread Tolerance Class: |
| 6g |
| Product Name: |
| Navy special project |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5732 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| M |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| <u>-</u> |
| Demilitarization: |
| |

No

NSN 5306-01-288-9350

Shear Bolt - Page 2 of 2



Fiig:

A003b0