

View Online at <https://aerobasegroup.com/nsn/5306-01-289-5009>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.044 inches

Fastener Length:

2.794 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

Between 0.422 inches and 0.437 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 1.740 inches and 1.760 inches

Thready Qty Per Inch (tpi):

24

Surface Finish:

32.0 microinches grip

Special Features:

9furnished with pawl ph13-8mo per ams5629; spring cres per qq-w-423 comp 302 or 304 cond b or 17-7ph per ams 5678; plug 300 series per astm a582; groove pin 300 series per 66; finish pawl dry film lub per mil-l-8937; spring wet abrasive blast 17-7 ph

Material:

Steel comp xm-13 fastener

Material Specification:

Ams 5629 assn standard single material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0