

View Online at <https://aerobasegroup.com/nsn/5306-01-289-5009>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.044 inches

**Fastener Length:**

2.794 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.378 inches and 0.398 inches

**Width Between Flats:**

Between 0.422 inches and 0.437 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

Between 0.081 inches and 0.101 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.740 inches and 1.760 inches

**Thready Qty Per Inch (tpi):**

24

**Surface Finish:**

32.0 microinches grip

**Special Features:**

9furnished with pawl ph13-8mo per ams5629; spring cres per qq-w-423 comp 302 or 304 cond b or 17-7ph per ams 5678; plug 300 series per astm a582; groove pin 300 series per 66; finish pawl dry film lub per mil-l-8937; spring wet abrasive blast 17-7 ph

**Material:**

Steel comp xm-13 fastener

**Material Specification:**

Ams 5629 assn standard single material response fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0