## NSN 5306-01-289-6931

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-289-6931 **Thread Direction:** Right-hand Thread Length: 16.0 millimeters Fastener Length: Between 21.70 millimeters and 22.30 millimeters **Head Style:** Undercut hexagon **Head Height:** Between 5.7 millimeters and 6.0 millimeters Width Between Flats: Between 18.67 millimeters and 19.00 millimeters **Grip Diameter:** Between 11.959 millimeters and 11.984 millimeters **Thread Diameter:** 12.0 millimeters **Grip Length:** Between 5.80 millimeters and 6.20 millimeters **Thread Pitch In Millimeters:** 1.25 **External Thread Tolerance Class:** 4h6h Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Mi **Specification Data:** 80205-na0036 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

No

A003b0

## NSN 5306-01-289-6931

Close Tolerance Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.