

View Online at <https://aerobasegroup.com/nsn/5306-01-289-6931>

Thread Direction:

Right-hand

Thread Length:

16.0 millimeters

Fastener Length:

Between 21.70 millimeters and 22.30 millimeters

Head Style:

Undercut hexagon

Head Height:

Between 5.7 millimeters and 6.0 millimeters

Width Between Flats:

Between 18.67 millimeters and 19.00 millimeters

Grip Diameter:

Between 11.959 millimeters and 11.984 millimeters

Thread Diameter:

12.0 millimeters

Grip Length:

Between 5.80 millimeters and 6.20 millimeters

Thread Pitch In Millimeters:

1.25

External Thread Tolerance Class:

4h6h

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0036 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.