

View Online at <https://aerobasegroup.com/nsn/5306-01-290-5767>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.453 inches

Fastener Length:

Between 3.250 inches and 3.281 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.678 inches and 0.690 inches

Grip Diameter:

Between 0.436 inches and 0.437 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 2.802 inches and 2.822 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000, g43406 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322, g8740 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Supplementary Features:

Intmd lg spec

Thread Series Designator:

Unjf

Specification Data:

80205-nas6207 professional/industrial association standard and 80205-nas1107/canceled/ professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.