

View Online at <https://aerobasegroup.com/nsn/5306-01-290-7450>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.682 inches and 0.732 inches

**Fastener Length:**

Between 1.567 inches and 1.597 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.395 inches and 0.415 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Extended Washer Diameter:**

Between 0.715 inches and 0.725 inches

**Extended Washer Thickness:**

Between 0.065 inches and 0.085 inches

**Hole Diameter:**

Between 0.065 inches and 0.075 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.865 inches and 0.885 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hole Configuration Style:**

Double hexagon flats

**Material:**

Cobalt comp mp-35-n

**Material Specification:**

Ams5844 assn standard single material response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0