

View Online at <https://aerobasegroup.com/nsn/5306-01-290-9335>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.323 inches

**Fastener Length:**

Between 7.246 inches and 7.276 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.188 inches and 0.190 inches

**End Application:**

Acft, model cp-140 aurora

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 6.928 inches and 6.948 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000, g43406 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322, g87400 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Supplementary Features:**

Intmd lg -111 /0.0625 in./ incr spec

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6203 professional/industrial association standard and 80205-nas1103/canceled/ professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.