NSN 5306-01-295-0082

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-295-0082

View Online at https://aerobasegroup.com/nsn/5306-01-295-0082
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.625 inches and 0.665 inches
Fastener Length:
Between 5.885 inches and 5.905 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
0.438 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 5.240 inches and 5.260 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-295-0082

Machine Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0