## NSN 5306-01-295-5620

Shear Bolt - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5306-01-295-5620



### 3a **Thread Direction: Right-hand Thread Length:** 0.323 inches **Fastener Length:** Between 5.058 inches and 5.088 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.188 inches and 0.190 inches **End Application:** Acft, model cp-140 aurora **Thread Diameter:** 0.190 inches Grip Length: Between 4.740 inches and 4.760 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000, g43406 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322, g87400 assn standard 2nd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas6203 professional/industrial association standard and 80205-nas1103/canceled/ professional/industrial association standard

# NSN 5306-01-295-5620

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

### Mil-std (military Standard):

Mil-s-5000 spec.

