

View Online at <https://aerobasegroup.com/nsn/5306-01-295-7597>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.553 inches and 0.603 inches

Fastener Length:

Between 1.001 inches and 1.031 inches

Head Style:

Dished hexagon

Head Height:

Between 0.188 inches and 0.203 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Locking Feature:

Strip threads

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 0.428 inches and 0.448 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

140000 pounds per square inch

Hardness Rating:

24.0 rockwell c fastener and 35.0 rockwell c fastener

Minimum Yield Strength:

85000 pounds per square inch

Surface Finish:

63.0 microinches grip

Material:

Plastic polyamide locking feature

Material Specification:

Ams 5732 assn standard single material response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas1226 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0