NSN 5306-01-296-6417

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-296-6417

view Online at https://aerobasegroup.com/hsil/5500-01-290-0417
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.881 inches and 0.931 inches
Fastener Length:
Between 1.891 inches and 1.921 inches
Head Style:
Double hexagon extended washer
Head Height:
0.530 inches
Width Between Flats:
Between 0.616 inches and 0.627 inches
Extended Washer Diameter:
Between 0.940 inches and 0.950 inches
Extended Washer Thickness:
0.098 inches
Grip Diameter:
Between 0.4785 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 0.990 inches and 1.010 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:

N/a

NSN 5306-01-296-6417

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

