

View Online at <https://aerobasegroup.com/nsn/5306-01-296-6421>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.299 inches and 1.329 inches

**Fastener Length:**

Between 3.424 inches and 3.454 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

0.711 inches

**Width Between Flats:**

Between 0.403 inches and 0.414 inches

**Extended Washer Diameter:**

Between 1.419 inches and 1.429 inches

**Extended Washer Thickness:**

0.175 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.745 inches and 0.748 inches

**Thread Diameter:**

0.750 inches

**Grip Length:**

2.125 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Minimum Yield Strength:**

145000 pounds per square inch

**Hole Configuration Style:**

Double hexagon flats

**Surface Finish:**

32.0 microinches grip

**Material:**

Cobalt comp mp-35-n

**Material Specification:**

Ams 5758 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0