

View Online at <https://aerobasegroup.com/nsn/5306-01-296-6421>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.299 inches and 1.329 inches

Fastener Length:

Between 3.424 inches and 3.454 inches

Head Style:

Double hexagon extended washer

Head Height:

0.711 inches

Width Between Flats:

Between 0.403 inches and 0.414 inches

Extended Washer Diameter:

Between 1.419 inches and 1.429 inches

Extended Washer Thickness:

0.175 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.745 inches and 0.748 inches

Thread Diameter:

0.750 inches

Grip Length:

2.125 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

260000 pounds per square inch

Minimum Yield Strength:

145000 pounds per square inch

Hole Configuration Style:

Double hexagon flats

Surface Finish:

32.0 microinches grip

Material:

Cobalt comp mp-35-n

Material Specification:

Ams 5758 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0