

View Online at <https://aerobasegroup.com/nsn/5306-01-297-7529>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.413 inches and 0.463 inches

Fastener Length:

Between 0.548 inches and 0.578 inches

Head Style:

Dished hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.115 inches and 0.135 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Plastic polyamide locking feature

Material Specification:

Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6305 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0