## NSN 5306-01-297-7529

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-297-7529

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.413 inches and 0.463 inches
Fastener Length:
Between 0.548 inches and 0.578 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Plastic polyamide locking feature
Material Specification:
Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response fastener
Thread Series Designator:
Unjf
Specification Data:
80205-nas6305 professional/industrial association standard
Shelf Life:

N/a

## NSN 5306-01-297-7529

Shear Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0