

View Online at <https://aerobasegroup.com/nsn/5306-01-298-0640>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.254 inches and 1.274 inches

Fastener Length:

4.014 inches

Head Style:

Double hexagon w/hole

Head Height:

0.808 inches

Width Between Flats:

0.9375 inches

Extended Washer Diameter:

Between 1.428 inches and 1.438 inches

Extended Washer Thickness:

0.198 inches

Concentric Hole Depth:

0.260 inches

Concentric Hole Diameter:

0.187 inches

Thread Diameter:

0.875 inches

Features Provided:

Casehardened

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Special Features:

Surface finish on shank and bearing surface of head 32.0 microinches

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.