

View Online at <https://aerobasegroup.com/nsn/5306-01-298-0640>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.254 inches and 1.274 inches

**Fastener Length:**

4.014 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.808 inches

**Width Between Flats:**

0.9375 inches

**Extended Washer Diameter:**

Between 1.428 inches and 1.438 inches

**Extended Washer Thickness:**

0.198 inches

**Concentric Hole Depth:**

0.260 inches

**Concentric Hole Diameter:**

0.187 inches

**Thread Diameter:**

0.875 inches

**Features Provided:**

Casehardened

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Special Features:**

Surface finish on shank and bearing surface of head 32.0 microinches

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.