NSN 5306-01-298-1292

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-298-1292

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 1.163 inches and 1.213 inches **Fastener Length:** Between 4.235 inches and 4.265 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.590 inches and 0.610 inches Width Between Flats: Between 0.797 inches and 0.812 inches **Extended Washer Diameter:** Between 1.384 inches and 1.394 inches **Extended Washer Thickness:** Between 0.098 inches and 0.118 inches **Grip Diameter:** Between 0.7480 inches and 0.7490 inches **Thread Diameter:** 0.750 inches **Grip Length:** Between 3.052 inches and 3.072 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 ty2 cl2 military specification single treatment response

Thread Series Designator:

Unjf

NSN 5306-01-298-1292

Shear Bolt - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: