

View Online at <https://aerobasegroup.com/nsn/5306-01-298-1293>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.338 inches and 1.388 inches

Fastener Length:

Between 6.723 inches and 6.753 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.690 inches and 0.710 inches

Width Between Flats:

Between 0.923 inches and 0.938 inches

Extended Washer Diameter:

Between 1.615 inches and 1.625 inches

Extended Washer Thickness:

Between 0.116 inches and 0.136 inches

Grip Diameter:

Between 0.8730 inches and 0.8740 inches

Thread Diameter:

0.875 inches

Grip Length:

Between 5.365 inches and 5.385 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 ty2 cl2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.