## NSN 5306-01-298-6979

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-298-6979

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.579 inches and 0.639 inches
Fastener Length:
Between 1.599 inches and 1.629 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Hole Diameter:
Hole Diameter: Between 0.050 inches and 0.060 inches
Between 0.050 inches and 0.060 inches
Between 0.050 inches and 0.060 inches <b>Grip Diameter:</b>
Between 0.050 inches and 0.060 inches <b>Grip Diameter:</b> Between 0.3740 inches and 0.3745 inches
Between 0.050 inches and 0.060 inches <b>Grip Diameter:</b> Between 0.3740 inches and 0.3745 inches <b>Thread Diameter:</b>
Between 0.050 inches and 0.060 inches <b>Grip Diameter:</b> Between 0.3740 inches and 0.3745 inches <b>Thread Diameter:</b> 0.375 inches
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter:  0.375 inches  Grip Length:
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter:  0.375 inches  Grip Length:  Between 0.990 inches and 1.010 inches
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter:  0.375 inches  Grip Length:  Between 0.990 inches and 1.010 inches  Hole Quantity:
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter:  0.375 inches  Grip Length:  Between 0.990 inches and 1.010 inches  Hole Quantity:
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter:  0.375 inches  Grip Length:  Between 0.990 inches and 1.010 inches  Hole Quantity:  1  Hole Type:
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter:  0.375 inches  Grip Length:  Between 0.990 inches and 1.010 inches  Hole Quantity:  1  Hole Type:  Drilled
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter:  0.375 inches  Grip Length:  Between 0.990 inches and 1.010 inches  Hole Quantity:  1  Hole Type:  Drilled  Thready Qty Per Inch (tpi):
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter:  0.375 inches  Grip Length:  Between 0.990 inches and 1.010 inches  Hole Quantity:  1  Hole Type:  Drilled  Thready Qty Per Inch (tpi):  24
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter: 0.375 inches  Grip Length:  Between 0.990 inches and 1.010 inches  Hole Quantity: 1  Hole Type:  Drilled  Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi):
Between 0.050 inches and 0.060 inches  Grip Diameter:  Between 0.3740 inches and 0.3745 inches  Thread Diameter:  0.375 inches  Grip Length:  Between 0.990 inches and 1.010 inches  Hole Quantity:  1  Hole Type:  Drilled  Thready Qty Per Inch (tpi):  24  Min. Tensile Strength (psi):  220000 pounds per square inch

Material:

Steel comp xm-13

**Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5306-01-298-6979

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0