## NSN 5306-01-298-7332

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-298-7332 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.508 inches and 0.558 inches **Fastener Length:** Between 5.330 inches and 5.360 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.965 inches Width Between Flats: Between 1.115 inches and 1.127 inches **Extended Washer Diameter:** Between 1.615 inches and 1.625 inches **Extended Washer Thickness:** 0.221 inches **Thread Diameter:** 0.875 inches **Grip Length:** Between 3.802 inches and 3.822 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 260000 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head Material: Cobalt comp mp-35-n **Material Specification:** Ams 5844 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5306-01-298-7332

Machine Bolt - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A003b0