## NSN 5306-01-298-7335

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-298-7335 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.975 inches and 1.025 inches **Fastener Length:** Between 2.485 inches and 2.515 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.600 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Extended Washer Diameter:** Between 1.055 inches and 1.065 inches **Extended Washer Thickness:** 0.118 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 1.490 inches and 1.510 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-01-298-7335

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0