NSN 5306-01-300-6362

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-300-6362

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.500 inches |
| Fastener Length: |
| Between 1.640 inches and 1.750 inches |
| |
| Head Style: |
| Double hexagon extended washer |
| Head Height: |
| 0.500 inches |
| Width Between Flats: |
| Between 0.493 inches and 0.502 inches |
| Extended Washer Diameter: |
| Between 0.735 inches and 0.750 inches |
| Extended Washer Thickness: |
| 0.129 inches |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| Between 0.210 inches and 0.250 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 13 |
| Min. Tensile Strength (psi): |
| 150000 pounds per square inch |
| Hardness Rating: |
| 33.0 rockwell c and 43.0 rockwell c |
| Material: |
| Steel |
| Material Specification: |
| Sae j429 gr8 assn standard single material response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5306-01-300-6362Machine Bolt - Page 2 of 2



Fiig:

A003b0