NSN 5306-01-300-7333

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-300-7333

Tilleau Class.
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.526 inches and 0.576 inches
Fastener Length:
Between 1.848 inches and 1.878 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Head Minor Diameter:
Between 0.360 inches and 0.375 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
·

Passivate

Surface Treatment:

NSN 5306-01-300-7333

Shear Bolt - Page 2 of 2



	Surface	Treatment	Specification:
--	---------	------------------	----------------

Qq-p-35 federal specification single treatment response or mil-c-83488 type 2 cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.