NSN 5306-01-300-7333

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-300-7333

| Tilleau Class. |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.526 inches and 0.576 inches |
| Fastener Length: |
| Between 1.848 inches and 1.878 inches |
| Head Style: |
| Spline extended washer |
| Head Height: |
| Between 0.302 inches and 0.322 inches |
| Extended Washer Diameter: |
| Between 0.575 inches and 0.585 inches |
| Extended Washer Thickness: |
| Between 0.035 inches and 0.055 inches |
| Hole Diameter: |
| Between 0.050 inches and 0.060 inches |
| Grip Diameter: |
| Between 0.3115 inches and 0.3120 inches |
| Head Minor Diameter: |
| Between 0.360 inches and 0.375 inches |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 1.302 inches and 1.322 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| · |

Passivate

Surface Treatment:

NSN 5306-01-300-7333

Shear Bolt - Page 2 of 2



| ourrace freatment opecincation | Surface | Treatment | Specification |
|--------------------------------|---------|------------------|----------------------|
|--------------------------------|---------|------------------|----------------------|

Qq-p-35 federal specification single treatment response or mil-c-83488 type 2 cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.