

View Online at <https://aerobasegroup.com/nsn/5306-01-300-8908>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.163 inches and 1.213 inches

**Fastener Length:**

Between 3.985 inches and 4.015 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.590 inches and 0.610 inches

**Width Between Flats:**

Between 0.797 inches and 0.812 inches

**Extended Washer Diameter:**

Between 1.384 inches and 1.394 inches

**Extended Washer Thickness:**

Between 0.098 inches and 0.118 inches

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 2.802 inches and 2.822 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp h11

**Material Specification:**

Ams6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837 ty2 cl2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.