NSN 5306-01-301-1330

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-301-1330

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.690 inches and 0.710 inches Fastener Length: Between 1.190 inches and 1.210 inches Head Style: Double hexagon Head Height: Between 0.177 inches and 0.197 inches Width Between Flats: 0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.3110 inches and 0.510 inches Thread Syley Frinch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell o and 43.0 rockwell o Material: Steel MaterialSpecification: Mills-Sc000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	
Thread Direction: Right-hand Thread Length: Between 0.690 inches and 0.710 inches Fastener Length: Between 1.190 inches and 1.210 inches Head Style: Double hexagon Head Height: Between 0.177 inches and 0.197 inches Width Between 1.177 inches and 0.197 inches Width Between 0.177 inches and 0.3120 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Oty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uns Shelf Life: N/a Unit Of Measure:	Thread Class:
Right-hand Thread Length: Between 0.690 inches and 0.710 inches Fastener Length: Between 1.190 inches and 1.210 inches Head Style: Double hexagon Head Height: Between 0.177 inches and 0.197 inches Width Between D.177 inches and 0.197 inches Width Between 0.177 inches and 0.3120 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thread Valy Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Materials Specification: Mili-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ung Shelf Life: N/a Unit Of Measure:	3a
Thread Length: Between 0.690 inches and 0.710 inches Fastener Length: Between 1.190 inches and 1.210 inches Head Style: Double hexagon Head Height: Between 0.177 inches and 0.197 inches Width Between Flats: 0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thread Outpet Per Inch (tpt): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uns Shelf Life: N/a Unit Of Measure:	Thread Direction:
Between 0.690 inches and 0.710 inches Fastener Length: Between 1.190 inches and 1.210 inches Head Style: Double hexagon Head Height: Between 0.177 inches and 0.197 inches Width Between Flats: 0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: Detween 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 millitary specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uns Shelf Life: N/a Unit Of Measure:	Right-hand
Fastener Length: Between 1.190 inches and 1.210 inches Head Style: Double hexagon Head Height: Between 0.177 inches and 0.197 inches Width Between Flats: 0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uns Shelf Life: N/a Unit Of Measure:	Thread Length:
Between 1.190 inches and 1.210 inches Head Style: Double hexagon Head Height: Between 0.177 inches and 0.197 inches Width Between 0.177 inches and 0.197 inches Width Between Flats: 0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Between 0.690 inches and 0.710 inches
Head Style: Double hexagon Head Height: Between 0.177 inches and 0.197 inches Width Between Flats: 0.561 inches Grip Dlameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Ung Shelf Life: N/a Unit Of Measure:	Fastener Length:
Double hexagon Head Height: Between 0.177 inches and 0.197 inches Width Between Flats: 0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mill-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Between 1.190 inches and 1.210 inches
Head Height: Between 0.177 inches and 0.197 inches Width Between Flats: 0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mill-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uns Shelf Life: N/a Unit Of Measure:	Head Style:
Between 0.177 inches and 0.197 inches Width Between Flats: 0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mili-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uns Shelf Life: N/a Unit Of Measure:	Double hexagon
Width Between Flats: 0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uns Shelf Life: N/a Unit Of Measure:	Head Height:
0.561 inches Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Between 0.177 inches and 0.197 inches
Grip Diameter: Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Cty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Width Between Flats:
Between 0.3110 inches and 0.3120 inches Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Uncy-2416, ty if federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	0.561 inches
Thread Diameter: 0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Grip Diameter:
0.3125 inches Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Between 0.3110 inches and 0.3120 inches
Grip Length: Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Thread Diameter:
Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	0.3125 inches
Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Grip Length:
Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Between 0.490 inches and 0.510 inches
Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Thready Qty Per Inch (tpi):
180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	24
Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Min. Tensile Strength (psi):
39.0 rockwell c and 43.0 rockwell c Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	180000 pounds per square inch
Material: Steel Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Hardness Rating:
Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	39.0 rockwell c and 43.0 rockwell c
Material Specification: Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Material:
Mil-s-5000 military specification single material response or ams 6485 assn standard single material response Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Steel
Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Material Specification:
Cadmium Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Mil-s-5000 military specification single material response or ams 6485 assn standard single material response
Surface Treatment Specification: Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Surface Treatment:
Qq-p-416, ty ii federal specification single treatment response Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Cadmium
Thread Series Designator: Uns Shelf Life: N/a Unit Of Measure:	Surface Treatment Specification:
Uns Shelf Life: N/a Unit Of Measure:	Qq-p-416, ty ii federal specification single treatment response
Shelf Life: N/a Unit Of Measure:	Thread Series Designator:
N/a Unit Of Measure: 	Uns
Unit Of Measure:	Shelf Life:
	N/a
 Demilitarization:	Unit Of Measure:
	 Demilitarization:

No

NSN 5306-01-301-1330

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.