## NSN 5306-01-301-4069

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-301-4069

| View Crimine at https://decissategreen/individues of coli 1000                              |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| Between 0.663 inches and 0.713 inches   |
| Fastener Length:  |
| Between 0.985 inches and 1.015 inches   |
| Head Style:   |
| Bevel-conical   |
| Head Diameter:  |
| Between 0.583 inches and 0.625 inches   |
| Head Height:  |
| Between 0.333 inches and 0.353 inches   |
| Hole Diameter:  |
| Between 0.070 inches and 0.075 inches   |
| Internal Drive Style:   |
| Hexagon   |
| Thread Diameter:  |
| 0.375 inches  |
| Width Across Flats:   |
| Between 0.376 inches and 0.379 inches   |
| Hole Quantity:  |
| 6   |
| Hole Type:  |
| Drilled   |
| Thready Qty Per Inch (tpi):   |
| 24  |
| Min. Tensile Strength (psi):  |
| 160000 pounds per square inch   |
| Hole Configuration Style:   |
| Round internal hexagon  |
| Material:   |
| Steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 3135 or steel comp 3140 |
| Surface Treatment:  |
| Cadmium and chromate  |
| Surface Treatment Specification:  |
| Qq-p-416 type 2 class 2 federal specification single treatment response                     |
| Thread Series Designator:   |
| Unjf  |
| Specification Data:   |
| 80205-nas146 professional/industrial association standard                                   |

## NSN 5306-01-301-4069

Internal Wrenching Bolt - Page 2 of 2



| _ |   |   |     | - |      |  |
|---|---|---|-----|---|------|--|
| C | h | Δ | Iŧ. |   | ife: |  |
|   |   |   |     |   |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0