## NSN 5306-01-301-4069

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-301-4069

View Crimine at https://decissategreen/individues of coli 1000
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.663 inches and 0.713 inches
Fastener Length:
Between 0.985 inches and 1.015 inches
Head Style:
Bevel-conical
Head Diameter:
Between 0.583 inches and 0.625 inches
Head Height:
Between 0.333 inches and 0.353 inches
Hole Diameter:
Between 0.070 inches and 0.075 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.376 inches and 0.379 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 3135 or steel comp 3140
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas146 professional/industrial association standard

## NSN 5306-01-301-4069

Internal Wrenching Bolt - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0