

View Online at <https://aerobasegroup.com/nsn/5306-01-303-0916>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.750 inches and 0.938 inches

**Fastener Length:**

Between 1.938 inches and 2.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.150 inches and 0.163 inches

**Width Between Flats:**

Between 0.428 inches and 0.438 inches

**Locking Feature:**

Strip threads

**Thread Diameter:**

0.250 inches

**Features Provided:**

Finished head

**Thread Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Color:**

Green locking feature

**Material:**

Steel comp 301 fastener or steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fastener or steel comp 314 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**