## NSN 5306-01-303-1627

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-303-1627 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.125 inches **Fastener Length:** 2.500 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.490 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Extended Washer Diameter:** 0.688 inches **Extended Washer Thickness:** Between 0.110 inches and 0.120 inches **Hole Diameter:** 0.070 inches **First Diameter From Head:** Between 0.399 inches and 0.409 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.315 inches and 1.375 inches **Thread Diameter:** 0.438 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Double hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 8740

**Material Specification:** 

Ams 6322 assn standard single material response

## NSN 5306-01-303-1627

Externally Relieved Body Bolt - Page 2 of 2



Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams 2400 assn standard single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0