NSN 5306-01-303-2421

Shear Bolt - Page 1 of 2

Between 0.769 inches and 0.799 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-303-2421

| Between 0.828 inches and 0.875 inches |
|---|
| Head Style: |
| Hexagon |
| Head Height: |
| 0.281 inches |
| Width Between Flats: |
| Between 0.490 inches and 0.502 inches |
| Hole Diameter: |
| 0.070 inches |
| Grip Diameter: |
| 0.484 inches |
| Thread Diameter: |
| 0.3125 inches |
| Grip Length: |
| Between 0.030 inches and 0.060 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 9260 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Hole Configuration Style: |
| Hexagon corners |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| |

NSN 5306-01-303-2421

Shear Bolt - Page 2 of 2

A003b0



| Thread Series Designator: |
|---|
| Unjf |
| Specification Data: |
| 80205-nas565 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |