## NSN 5306-01-303-4052



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-303-4052 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.762 inches **Fastener Length:** 1.137 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.300 inches Width Between Flats: 0.312 inches **Extended Washer Diameter:** Between 0.428 inches and 0.438 inches **Extended Washer Thickness:** 0.069 inches **Grip Diameter:** 0.249 inches **Thread Diameter:** 0.250 inches **Grip Length:** 0.375 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150 **Material Specification:** Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response or mil-s-8503 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** 

Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5306-01-303-4052

Shear Bolt - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.