

View Online at <https://aerobasegroup.com/nsn/5306-01-303-9648>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 20.0 millimeters and 21.0 millimeters

**Fastener Length:**

Between 26.2 millimeters and 26.8 millimeters

**Head Style:**

Spline extended washer

**Head Height:**

Between 10.2 millimeters and 10.7 millimeters

**Extended Washer Diameter:**

18.4 millimeters

**Extended Washer Thickness:**

Between 2.5 millimeters and 2.8 millimeters

**Grip Diameter:**

Between 9.972 millimeters and 9.987 millimeters

**Head Minor Diameter:**

10.1 millimeters

**Thread Diameter:**

10.0 millimeters

**Grip Length:**

Between 5.8 millimeters and 6.2 millimeters

**Min. Tensile Strength (psi):**

1250 megapascals

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Thread Pitch In Millimeters:**

1.25

**External Thread Tolerance Class:**

4h6h

**Surface Finish:**

0.8 micrometers threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams5732 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Mj

**Specification Data:**

80205-na0059 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0