

View Online at <https://aerobasegroup.com/nsn/5306-01-303-9648>

Thread Direction:

Right-hand

Thread Length:

Between 20.0 millimeters and 21.0 millimeters

Fastener Length:

Between 26.2 millimeters and 26.8 millimeters

Head Style:

Spline extended washer

Head Height:

Between 10.2 millimeters and 10.7 millimeters

Extended Washer Diameter:

18.4 millimeters

Extended Washer Thickness:

Between 2.5 millimeters and 2.8 millimeters

Grip Diameter:

Between 9.972 millimeters and 9.987 millimeters

Head Minor Diameter:

10.1 millimeters

Thread Diameter:

10.0 millimeters

Grip Length:

Between 5.8 millimeters and 6.2 millimeters

Min. Tensile Strength (psi):

1250 megapascals

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Thread Pitch In Millimeters:

1.25

External Thread Tolerance Class:

4h6h

Surface Finish:

0.8 micrometers threads

Material:

Iron alloy 660

Material Specification:

Ams5732 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Mj

Specification Data:

80205-na0059 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0