## NSN 5306-01-304-2488

Shear Bolt - Page 1 of 2

**Thread Class:** 

3a

View Online at https://aerobasegroup.com/nsn/5306-01-304-2488



**Thread Direction: Right-hand Thread Length:** Between 0.589 inches and 0.639 inches Fastener Length: Between 2.036 inches and 2.066 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches Head Minor Diameter: Between 0.448 inches and 0.455 inches **Thread Diameter:** 0.375 inches Grip Length: Between 1.427 inches and 1.447 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Passivate

## NSN 5306-01-304-2488

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0