

View Online at <https://aerobasegroup.com/nsn/5306-01-304-5327>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.014 inches and 1.064 inches

Fastener Length:

Between 5.649 inches and 5.679 inches

Head Style:

Dished hexagon

Head Height:

Between 0.375 inches and 0.390 inches

Width Between Flats:

Between 1.052 inches and 1.062 inches

Locking Feature:

Patch threads

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Thread Diameter:

0.750 inches

Grip Length:

Between 4.615 inches and 4.635 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Plastic polyamide locking feature

Material Specification:

Mil-f-18240 military specification single material response locking feature

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6712 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.